

## SPECIFICATIONS

Model	Horsepower	Unit Weight	Nominal CFM Capacity
SHN-6-XB	–	85 lbs./38 kg	400 to 750
SHN-6	1/2	175 lbs./79 kg	400 to 750
SHN-6-M	1/2	265 lbs./120 kg	400 to 750
SHN-10-XB	–	120 lbs./54 kg	1,000 to 1,250
SHN-10	1/2	215 lbs./97 kg	1,000 to 1,250
SHN-10-H	1	225 lbs./102 kg	1,000 to 1,250
SHN-10-M	1/2	335 lbs./152 kg	1,000 to 1,250
SHN-10-HM	1	345 lbs./156 kg	1,000 to 1,250
SHN-20-XB	–	200 lbs./90 kg	2,000 to 2,500
SHN-20	1	324 lbs./147 kg	2,000 to 2,500
SHN-20-H	2	340 lbs./155 kg	2,000 to 2,500
SHN-20-M	1	524 lbs./237 kg	2,000 to 2,500
SHN-20-HM	2	540 lbs./244 kg	2,000 to 2,500
SHN-40-XB	–	344 lbs./156 kg	4,000 to 5,000
SHN-40	3	680 lbs./309 kg	4,000 to 5,000
SHN-40-H	5	691 lbs./314 kg	4,000 to 5,000
SHN-40-M	3	1,024 lbs./464 kg	4,000 to 5,000
SHN-40-HM	5	1,035 lbs./469 kg	4,000 to 5,000
SHN-40-HH	7-1/2	710 lbs./323 kg	2,500 to 5,500
SHN-50-T	3	660 lbs./300 kg	4,000 to 5,200
SG-2-XB	–	250 lbs./113 kg	2,200 to 3,000
SG-2	2	400 lbs./181 kg	2,200 to 3,000
SG-2-H	3	400 lbs./182 kg	2,200 to 3,000
SG-2-M	2	650 lbs./294 kg	2,200 to 3,000
SG-2-HM	3	650 lbs./294 kg	2,200 to 3,000
SG-4-XB	–	375 lbs./170 kg	4,000 to 6,000
SG-4	3	730 lbs./341 kg	4,000 to 6,000
SG-4-H	5	825 lbs./375 kg	4,000 to 6,000
SG-4-HH	7-1/2	850 lbs./385 kg	4,000 to 6,000
SG-4-M	3	1,150 lbs./385 kg	4,000 to 6,000
SG-4-HM	5	1,150 lbs./385 kg	4,000 to 6,000
SG-4-HHM	7-1/2	1,200 lbs./543 kg	4,000 to 6,000
SG-4-T	3	825 lbs./375 kg	4,000 to 6,000
SG-4-TH	5	825 lbs./375 kg	4,000 to 6,000
SG-6-XB	–	550 lbs./249 kg	6,600 to 9,000
SG-6	7-1/2	1,100 lbs./498 kg	6,600 to 9,000
SG-6-H	10	1,125 lbs./509 kg	6,600 to 9,000
SG-6-M	7-1/2	1,625 lbs./735 kg	6,600 to 9,000
SG-6-HM	10	1,625 lbs./735 kg	6,600 to 9,000

Customized configurations are available. Contact UAS Factory for more information.

H: High Static  
 HH: Higher Static  
 M: Multiple-Pass or Tandem  
 T: T-Shape Configuration  
 XB: No Motor/Blower