



SMOGHOG IMPINGEMENT/FIRE STOP MODULE SPECIFICATION								
UA-XB MODEL No	NOMINAL AIRFLOW L/sec	PRESSURE DROP PASCALS	B	C	D	E	FILTERS's CARBON	UNIT WEIGHT Kg's
UA11	520	400	578	477	594	493	1.5	9
UA12	1040	400	1108	1007	594	493	3	18
UA22	2080	400	1108	1007	1188	1087	6	36
UA32	1120	400	1108	1007	1783	1682	9	54
UA42	4160	400	1108	1007	2376	2276	12	72
UA52	5200	400	1108	1007	2973	2870	15	90
UA13	1560	400	1634	1532	594	493	4.5	24.5
UA23	3120	400	1634	1532	1188	1087	9	49
UA33	4680	400	1634	1532	1783	1682	13.5	73.5
UA43	6240	400	1634	1532	2376	2276	18	98
UA53	7800	400	1634	1532	2972	2870	22.5	122.5
UA14	2080	400	2216	2015	594	493	6	36
UA24	4160	400	2216	2015	1188	1087	12	72
UA34	6240	400	2216	2015	1783	1682	18	108
UA44	8320	400	2216	2015	2376	2276	24	144
UA54	10400	400	2216	2015	2972	2870	30	180
UA16	3120	400	3267	3066	594	493	9	49
UA26	6240	400	3267	3066	1188	1087	18	98
UA36	9360	400	3267	3066	1783	1682	27	147
UA46	12480	400	3267	3066	2376	2276	36	196
UA56	15600	400	3267	3066	2972	2870	45	245

